

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Trade name : 65% Ethanol  
Product code : 8073  
Type of product : Food Safety -- [Food Safety]  
Part Number(s) : 8073|8074|700002492|700002493

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Scientific research and development  
Laboratory chemicals

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Neogen Corporation  
620 Leshner Place  
48912 Lansing – Michigan  
United States of America  
T 800.234.5333  
[sds@neogen.com](mailto:sds@neogen.com) - <https://www.neogen.com/>

### 1.4. Emergency telephone number

Emergency number : 24 hours:  
Medical: 1-800-498-5743 (U.S. and Canada) or 1-651-523-0318 (international)  
Spill/CHEMTREC: 1-800-424-9300 (U.S. and Canada) or 1-703-527-3887 (international)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to GB CLP (SI 2019:720 as amended)

Flammable liquids, Category 2 H225  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity – Single exposure, Category 2 H371  
Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP) :



Signal word (GB CLP) : Danger  
Contains : Methanol  
Hazard statements (GB CLP) : H225 - Highly flammable liquid and vapour.  
H319 - Causes serious eye irritation.  
H371 - May cause damage to organs.

# 65% Ethanol

## Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Precautionary statements (GB CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating and lighting equipment.  
P260 - Do not breathe dust, fume, gas, mist, vapours or spray.  
P264 - Wash hands, forearms and face thoroughly after handling.

### 2.3. Other hazards

#### Results of PBT and vPvB assessment

Component	
Substance(s) not meeting the PBT criteria of UK REACH regulation, in accordance with Annex XIII	Isopropanol (67-63-0), Methanol (67-56-1), Ethanol (64-17-5)
Substance(s) not meeting the vPvB criteria of UK REACH regulation, in accordance with Annex XIII	Isopropanol (67-63-0), Methanol (67-56-1), Ethanol (64-17-5)

#### Results of Endocrine Disruptor assessment

Component	
Substance(s) not considered as endocrine disrupting. They are not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, nor identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP	Ethanol(64-17-5), Isopropanol(67-63-0), Methanol(67-56-1)

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
Ethanol substance with workplace exposure limit(s)	CAS-No.: 64-17-5 EC-No.: 200-578-6	50 – 75	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Isopropanol substance with workplace exposure limit(s)	CAS-No.: 67-63-0 EC-No.: 200-661-7	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Methanol substance with workplace exposure limit(s)	CAS-No.: 67-56-1 EC-No.: 200-659-6	1 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 (ATE=1400 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) STOT SE 1, H370

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Self protection of the first-aiders : First aid workers will be equipped with suitable personal protective equipment.

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

No additional information available

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

No additional information available

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

No additional information available

### 6.3. Methods and material for containment and cleaning up

No additional information available

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

No additional information available

### 7.2. Conditions for safe storage, including any incompatibilities

No additional information available

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Isopropanol (67-63-0)	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m <sup>3</sup>
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m <sup>3</sup>
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Methanol (67-56-1)	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Methanol
WEL TWA (OEL TWA)	266 mg/m <sup>3</sup>
	200 ppm
WEL STEL (OEL STEL)	333 mg/m <sup>3</sup>
	250 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Ethanol (64-17-5)	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethanol
WEL TWA (OEL TWA)	1920 mg/m <sup>3</sup>
	1000 ppm
WEL STEL (OEL STEL)*	5760 mg/m <sup>3</sup>
	3000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
	*STEL value is calculated based on the TWA limit

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

### 8.2.2. Personal protection equipment

#### 8.2.2.1. Eye and face protection

No additional information available

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

### 8.2.2.2. Skin protection

No additional information available

### 8.2.2.3. Respiratory protection

No additional information available

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Odour	: Alcoholic.
Odour threshold	: Not available
pH	: Not available
Melting point	: -114.1 °C
Freezing point	: Not available
Boiling point	: 78.29 °C
Flash point	: 21.5 °C
Flammability	: Not available
Lower explosion limit	: 3.1 Vol-%
Upper explosion limit	: 27.7 Vol-%
Vapour pressure	: 59.27 mm Hg
Vapour pressure at 50°C	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: 0.79
Density	: Not available
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: 400 °C
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Explosive properties	: Not available

### 9.2. Other information

Particle characteristics : Not applicable

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

#### Isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 oral	4384 mg/kg
LD50 dermal rabbit	13120 mg/kg bw/day (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Converted value, Dermal, 14 day(s))
LD50 dermal	12870 mg/kg
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

#### Methanol (67-56-1)

LD50 oral rat	1187 – 2769 mg/kg bodyweight (BASF test, Rat, Male / female, Experimental value, 15-35 % aqueous solution, Oral, 7 day(s))
LD50 oral	1400 mg/kg
LD50 dermal rabbit	17100 mg/kg (Rabbit, Experimental value, Dermal)
LD50 dermal	15800 mg/kg
LC50 Inhalation - Rat	128.2 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

#### Ethanol (64-17-5)

LD50 oral rat	10470 mg/kg (Rat, male and female) (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg rabbit, OECD Test Guideline 402
LC50 Inhalation - Rat	51 mg/l (Rat; 4 h; vapour) (OECD Test Guideline 403)

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)

#### Isopropanol (67-63-0)

pH	No data available in the literature
----	-------------------------------------

#### Methanol (67-56-1)

pH	No data available in the literature
----	-------------------------------------

Serious eye damage/irritation : Causes serious eye irritation.

#### Isopropanol (67-63-0)

pH	No data available in the literature
----	-------------------------------------

#### Methanol (67-56-1)

pH	No data available in the literature
----	-------------------------------------

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)  
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)  
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Ethanol (64-17-5)	
NOAEL (chronic, oral, animal/male, 2 years)	> 4250 mg/kg bodyweight (Mouse, male)(Target Organs: Liver)(Oral; 105 weeks; Frequency of treatment: 5 days/week)(OPPTS 870.4200)
NOAEL (chronic, oral, animal/female, 2 years)	> 4000 mg/kg bodyweight (Mouse, female)(Target Organs: Liver)(Oral; 105 weeks; Frequency of treatment: 5 days/week)
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Methanol (67-56-1)	
LOAEL (animal/male, F0/P)	2340 mg/kg bodyweight Monkey, Male, 3 days, daily dose
Ethanol (64-17-5)	
NOAEL (animal/male, F1)	13.8 (Mouse, male and female)(OECD Test Guideline 416)Reduction in sperm motility.
NOAEL (animal/female, F1)	13.8 (Mouse, male and female)(OECD Test Guideline 416)Reduction in sperm motility.
STOT-single exposure	: May cause damage to organs.
Isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Ethanol (64-17-5)	
LOAEL (oral, rat, 90 days)	3160 mg/kg bodyweight/day
NOAEL (oral, rat, 28 days)	1730 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	3160 mg/kg bodyweight/day
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Isopropanol (67-63-0)	
Viscosity, kinematic	2.66 mm <sup>2</sup> /s (25 °C, Estimated value)
Methanol (67-56-1)	
Viscosity, kinematic	0.68 – 0.747 mm <sup>2</sup> /s
Other information	
No additional information available	
SECTION 12: Ecological information	
12.1. Toxicity	
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)
Isopropanol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Isopropanol (67-63-0)	
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1000 mg/l
ErC50 algae	1000 mg/l
NOEC chronic crustacea	100 mg/l

Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'

### 12.2. Persistence and degradability

65% Ethanol	
Persistence and degradability	Not rapidly degradable

Isopropanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.2 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.2 g O <sub>2</sub> /g substance
ThOD	2.4 g O <sub>2</sub> /g substance

Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.1 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.4 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance

Ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.

### 12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Methanol (67-56-1)	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

### 12.4. Mobility in soil

#### Isopropanol (67-63-0)

Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.19 – 0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

#### Methanol (67-56-1)

Mobility in soil	2.75 Source: HSDB
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Results of PBT and vPvB assessment

#### Component

Isopropanol (67-63-0)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Methanol (67-56-1)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Ethanol (64-17-5)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII

### 12.6. Other adverse effects

Ozone : Not classified (Based on available data, the classification criteria are not met)

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

HP Code : HP3 - "Flammable:"  
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;  
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;  
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;  
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;  
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;  
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.  
HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.  
HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.






## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

# 65% Ethanol

## Safety Data Sheet


According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1987	UN 1987	UN 1987	UN 1987	UN 1987
<b>14.2. UN proper shipping name</b>				
ALCOHOLS, N.O.S. Denatured alcohol	ALCOHOLS, N.O.S. Denatured alcohol	Alcohols, n.o.s. Denatured alcohol	ALCOHOLS, N.O.S. Denatured alcohol	ALCOHOLS, N.O.S. Denatured alcohol
<b>Transport document description</b>				
UN 1987 ALCOHOLS, N.O.S. Denatured alcohol, 3, II, (D/E)	UN 1987 ALCOHOLS, N.O.S. Denatured alcohol, 3, II	UN 1987 Alcohols, n.o.s. Denatured alcohol, 3, II	UN 1987 ALCOHOLS, N.O.S. Denatured alcohol, 3, II	UN 1987 ALCOHOLS, N.O.S. Denatured alcohol, 3, II
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
II	II	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640C
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: L1.5BN
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

#### Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: B

### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A180
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 601, 640C
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601, 640C
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: L1.5BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. National regulations

##### UK REACH Annex XVII (Restriction List)

This product contains no substance(s) listed on UK REACH Annex XVII (Restriction List) equal to or above the level of SDS disclosure

##### UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

##### UK REACH Candidate List (SVHC)

This product contains no substance(s) listed on the UK REACH Candidate List (SVHC).

# 65% Ethanol

## Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

### GB PIC Regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

### POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

### Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

### Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a reportable explosive precursor on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

### Drug Precursors Regulation (EC 273/2004)

This product contains no substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure

#### 15.1.2. Other Information

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H371	May cause damage to organs.

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.