

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : 70% Methanol
Product code : 8055

1.2. Other means of identification

Part Number(s) : 8055|8056|700002488|700002489

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Scientific research and development, Laboratory chemicals

1.4. Supplier's details

Neogen Corporation
620 Leshar Place
Lansing, Michigan 48912
United States of America
T 800.234.5333
sds@neogen.com - <https://www.neogen.com/>

1.5. Emergency phone number

Emergency number : 24 hours:
Medical: 1-800-498-5743 (U.S. and Canada) or 1-651-523-0318 (international)
Spill/CHEMTREC: 1-800-424-9300 (U.S. and Canada) or 1-703-527-3887 (international)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2	H225	Highly flammable liquid and vapor.
Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Acute toxicity (dermal), Category 3	H311	Toxic in contact with skin.
Acute toxicity (inhalation:dust,mist), Category 3	H331	Toxic if inhaled.
Specific target organ toxicity — Single exposure, Category 1	H370	Causes damage to organs.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H311+H331 - Toxic in contact with skin or if inhaled
H370 - Causes damage to organs.
Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P311 - If exposed or concerned: Call a poison center or doctor.
P311 - Call a poison center or doctor.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Methanol	CAS-No.: 67-56-1	50 – 75	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Harmful if swallowed.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Methanol
ACGIH® TLV® TWA	262 mg/m ³
	200 ppm
ACGIH® TLV® STEL	328 mg/m ³
	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
USA - ACGIH - Biological Exposure Indices	
Local name	Methanol
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns
Regulatory reference	ACGIH 2025

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Methanol (67-56-1)	
USA - OSHA - Occupational Exposure Limits	
Local name	Methyl alcohol
OSHA PEL TWA	260 mg/m ³
	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Methyl alcohol; methanol
Cal/OSHA PEL (OEL TWA)	260 mg/m ³
	200 ppm
Cal/OSHA STEL	325 mg/m ³
	250 ppm
Cal/OSHA C	1000 ppm
Remark (Cal/OSHA)	S - Skin notation and Protecting Clothing
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Methyl alcohol
NIOSH REL 10h TWA	200 ppm
NIOSH REL STEL	250 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Clear
Odor	: alcoholic
Odor threshold	: 100 ppm
pH	: No data available
Melting point	: -97.6 °C
Freezing point	: No data available
Boiling point	: 64 – 65 °C
Flash point	: 16 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 127 mm Hg
Relative vapor density at 20°C	: No data available
Relative density	: 0.792
Density	: 1.11
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: 440 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: 0.486 mm ² /s
Viscosity, dynamic	: 0.54 mPa·s
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Toxic in contact with skin.
Acute toxicity (inhalation) : Inhalation:dust,mist: Toxic if inhaled.

70% Methanol	
ATE US (oral)	1695.714 mg/kg body weight
ATE US (dermal)	428.571 mg/kg body weight
ATE US (dust, mist)	0.714 mg/l/4h

Methanol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, 15-35 % aqueous solution, Oral, 7 day(s))
LD50 oral	1400 mg/kg
LD50 dermal rabbit	17100 mg/kg (Rabbit, Experimental value, Dermal)
LD50 dermal	15800 mg/kg
LC50 Inhalation - Rat	128.2 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1187 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Skin corrosion/irritation : Not classified

Methanol (67-56-1)	
pH	No data available in the literature

Serious eye damage/irritation : Not classified

Methanol (67-56-1)	
pH	No data available in the literature

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Methanol (67-56-1)	
LOAEL (animal/male, F0/P)	2340 mg/kg body weight Monkey, Male, 3 days, daily dose

STOT-single exposure : Causes damage to organs.

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

70% Methanol	
Viscosity, kinematic	0.486 mm ² /s

Methanol (67-56-1)	
Viscosity, kinematic	0.68 – 0.747 mm ² /s

Symptoms/effects after inhalation : Toxic if inhaled.
Symptoms/effects after skin contact : Toxic in contact with skin.
Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : Harmful if swallowed.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'

12.2. Persistence and degradability

70% Methanol	
Persistence and degradability	Not rapidly degradable

Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.1 g O ₂ /g substance
Chemical oxygen demand (COD)	1.4 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.3. Bioaccumulative potential

Methanol (67-56-1)	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Methanol (67-56-1)	
Mobility in soil	2.75 Source: HSDB
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects





Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapors may accumulate in the container. Do not re-use empty containers.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1230	UN1230	1230	1230
14.2. Proper Shipping Name			
Methanol	METHANOL	METHANOL	Methanol
14.3. Transport hazard class(es)			
3 (6.1)	3 (6.1)	3 (6.1)	3 (6.1)
			
14.4. Packing group			
II	II	II	II

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	TDG	IMDG	IATA
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT	
UN-No. (DOT)	: UN1230
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
TDG	
UN-No. (TDG)	: UN1230
TDG Special Provisions	: 43 - Despite section 2.1 of Part 2 (Classification), these dangerous goods are assigned to this classification based on human experience.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 1 L
Emergency Response Guide (ERG) Number	: 131
IMDG	
Special provision (IMDG)	: 279
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Tank special provisions (IMDG)	: TP2
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Flash point (IMDG)	: 12°C c.c.
Properties and observations (IMDG)	: Colorless, volatile liquid. Flashpoint: 12°C c.c. Explosive limits: 6% to 36.5%. Miscible with water. Toxic if swallowed; may cause blindness. Avoid skin contact.

IATA

Special provision (IATA)	: A113
PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 352
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 3L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are exempt or present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methanol	CAS-No. 67-56-1	50 – 75%
----------	-----------------	----------

Methanol (67-56-1)


Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

No additional information available

15.3. State regulations

 **WARNING:** This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date	: 8/25/2025
Issue date	: 3/26/2025

70% Methanol

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.