

SECTION 1 Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : 70% Methanol
Type of product : Food Safety -- [Food Safety]
Product code : 8055

1.2. Other means of identification

Part Number(s) : 8055|8056|700002488|700002489

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Scientific research and development, Laboratory chemicals

1.4. Supplier's details

Neogen Corporation
620 Leshar Place
Lansing, Michigan 48912
United States of America
T 800.234.5333
sds@neogen.com - <https://www.neogen.com/>

1.5. Emergency phone number

Emergency number : 24 hours:
Medical: 1-800-498-5743 (U.S. and Canada) or 1-651-523-0318 (international)
Spill/CHEMTREC: 1-800-424-9300 (U.S. and Canada) or 1-703-527-3887 (international)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable liquids, Category 2	H225	Highly flammable liquid and vapor.
Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Acute toxicity (inhalation:dust,mist), Category 3	H331	Toxic if inhaled.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child.
Specific target organ toxicity, Single exposure, Category 1	H370	Causes damage to organs.
Specific target organ toxicity, Repeated exposure, Category 1	H372	Causes damage to organs through prolonged or repeated exposure.

Full text of H statements : see section 16

2.2. GHS label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hazard statements (GHS CA)	: H225 - Highly flammable liquid and vapor H302 - Harmful if swallowed H319 - Causes serious eye irritation H331 - Toxic if inhaled H360 - May damage fertility or the unborn child H370 - Causes damage to organs. H372 - Causes damage to organs through prolonged or repeated exposure.
Precautionary statements (GHS CA)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe dust, fume, gas, mist, vapors, spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P311 - IF exposed or concerned: Call a POISON CENTER or a doctor. P308+P313 - IF exposed or concerned: Get medical advice or attention. P311 - Call a POISON CENTER or a doctor. P314 - Get medical advice or attention if you feel unwell. P321 - Specific treatment (see supplemental first aid instruction on this label). P330 - Rinse mouth. P337+P313 - If eye irritation persists: Get medical advice or attention. P370+P378 - In case of fire: Use appropriate media to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Methanol	Methylalcohol 420A reagent #5 / acetone alcohol / A13-00409 / alcohol C1 / alcohol, methyl / carbinol / caswell No 552 / coat- B1400 / colonial spirit / colonial spirits / columbian spirit / columbian spirits / EPA pesticide chemical code 053801 / eureka products criosine disinfectant / eureka products, criosine / freers elm arrester / green wood spirits / holzin / HYDRANAL- standard- methanol / ideal concentrated wood preservative / manhattan spirits / methanol / methanol chromasol / methyl alcohol / methyl hydrate / methyl hydroxide / methylen / methylol / monohydroxymet hane / pyroligneous spirit / pyroxylic spirit / RCRA waste number U154 / standard wood spirits / surflo-B17 / wilbur-ellis smut- guard / wood alcohol / wood naphtha / wood spirit / X-cide 402 industrial bactericide	CAS-No.: 67-56-1	≥ 50 – < 75	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:gas), H331 Acute Tox. 3 (Inhalation:dust,mist), H331 Eye Irrit. 2, H319 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Full text of hazard classes and H-statements : see section 16

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Harmful if swallowed.
Chronic symptoms	: May damage fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
Environmental precautions	: Avoid release to the environment. Notify authorities if product enters sewers or public waters.

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

6.2. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.
- For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Methanol (Methyl alcohol)
OEL TWA	262 mg/m ³
	200 ppm
OEL STEL	328 mg/m ³
	250 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Methyl alcohol (Methanol)
VECD (OEL STEV)	328 mg/m ³
	250 ppm
VEMP (OEL TWA EV)	262 mg/m ³
	200 ppm
Notations and remarks	Pc

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Methanol (67-56-1)	
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin (the substance that contribute significantly to the overall exposure by the skin route)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m ³ 200 ppm
OEL STEL	328 mg/m ³ 250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Headache; eye dam; dizziness; nausea
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m ³ 200 ppm
OEL STEL	328 mg/m ³ 250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m ³ 200 ppm
OEL STEL	328 mg/m ³ 250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Methanol (67-56-1)	
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Methanol
OEL TWAEV	200 ppm
	250 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m ³
	200 ppm
OEL STEL	328 mg/m ³
	250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Clear
Odor	: alcoholic
Odor threshold	: 100 ppm
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: -97.6 °C
Freezing point	: No data available
Boiling point	: 64 – 65 °C
Flash point	: 16 °C
Auto-ignition temperature	: 440 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 127 mm Hg
Relative vapor density at 20°C	: No data available
Relative density	: 0.792
Density	: 1.11
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 0.486 mm ² /s
Viscosity, dynamic	: 0.54 mPa·s
Explosion limits	: No data available
Particle characteristics	: No data available

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: Highly flammable liquid and vapor.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Inhalation:dust,mist: Toxic if inhaled.

70% Methanol	
ATE CA (oral)	1695.714 mg/kg body weight
ATE CA (dust,mist)	0.714 mg/l/4h

Methanol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, 15-35 % aqueous solution, Oral, 7 day(s))
LD50 oral	1400 mg/kg
LD50 dermal rabbit	17100 mg/kg (Rabbit, Experimental value, Dermal)
LD50 dermal	15800 mg/kg
LC50 Inhalation - Rat	128.2 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE CA (oral)	1187 mg/kg body weight
ATE CA (Dermal)	15800 mg/kg body weight
ATE CA (Gases)	700 ppmV/4h
ATE CA (vapors)	3 mg/l/4h
ATE CA (dust,mist)	0.5 mg/l/4h

Skin corrosion/irritation : Not classified

Methanol (67-56-1)	
pH	No data available in the literature

Serious eye damage/irritation : Causes serious eye irritation.

Methanol (67-56-1)	
pH	No data available in the literature

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Carcinogenicity : Not classified
Reproductive toxicity : May damage fertility or the unborn child.

Methanol (67-56-1)

LOAEL (animal/male, F0/P)	2340 mg/kg body weight Monkey, Male, 3 days, daily dose
---------------------------	---

STOT-single exposure : Causes damage to organs.

Methanol (67-56-1)

STOT-single exposure	Causes damage to organs.
----------------------	--------------------------

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Methanol (67-56-1)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified

70% Methanol

Viscosity, kinematic	0.486 mm ² /s
----------------------	--------------------------

Methanol (67-56-1)

Viscosity, kinematic	0.68 – 0.747 mm ² /s
----------------------	---------------------------------

Symptoms/effects after inhalation : Toxic if inhaled.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Harmful if swallowed.
Chronic symptoms : May damage fertility or the unborn child.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Methanol (67-56-1)

LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

70% Methanol

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.1 g O ₂ /g substance
Chemical oxygen demand (COD)	1.4 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance

12.3. Bioaccumulative potential

Methanol (67-56-1)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)

12.4. Mobility in soil

Methanol (67-56-1)	
Mobility in soil	2.75 Source: HSDB
Surface tension	No data available in the literature
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapors may accumulate in the container. Do not re-use empty containers.

SECTION 14 Transport information





In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
UN1230	UN1230	1230	1230
14.2. UN Proper Shipping Name			
METHANOL	Methanol	METHANOL	Methanol
Transport document description			
UN1230 METHANOL, 3 (6.1), II	UN1230 Methanol, 3 (6.1), II	UN 1230 METHANOL, 3 (6.1), II (12°C c.c.)	UN 1230 Methanol, 3 (6.1), II

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

TDG	DOT	IMDG	IATA
14.3. Transport hazard class(es)			
3 (6.1)	3 (6.1)	3 (6.1)	3 (6.1)
			
14.4. Packing group, if applicable			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

TDG

UN-No. (TDG)	: UN1230
TDG Special Provisions	: 43 - Despite section 2.1 of Part 2 (Classification), these dangerous goods are assigned to this classification based on human experience.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 1 L
Emergency Response Guide (ERG) Number	: 131

DOT

UN-No. (DOT)	: UN1230
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

IMDG	
Special provision (IMDG)	: 279
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP2
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Flash point (IMDG)	: 12°C c.c.
Properties and observations (IMDG)	: Colorless, volatile liquid. Flashpoint: 12°C c.c. Explosive limits: 6% to 36.5%. Miscible with water. Toxic if swallowed; may cause blindness. Avoid skin contact.

IATA	
PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 352
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A113
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16 Other Information

Issue date	: 08-12-2025
Revision date	: 08-12-2025
Supersedes	: 08-12-2025

Full text of hazard classes and H-statements:

H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H319	Causes serious eye irritation

70% Methanol

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Full text of hazard classes and H-statements:

H331	Toxic if inhaled
H360	May damage fertility or the unborn child
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.