

### SECTION 1 Identification

#### 1.1. GHS Product identifier

Product form	: Mixture
Trade name	: Ideal® Prima® Spray-On Glo-Fluorescent Orange
Type of product	: Animal Safety -- [Animal Safety]
Product code	: 338389

#### 1.2. Other means of identification

Part Number(s) : 338389

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Animal marking ink  
Restrictions on use : For animal use only

#### 1.4. Supplier's details

##### Supplier

Neogen Corporation  
620 Leshar Place  
Lansing, Michigan 48912  
United States of America  
T 800.234.5333  
[sds@neogen.com](mailto:sds@neogen.com) - <https://www.neogen.com/>

#### 1.5. Emergency phone number

Emergency number : 24 hours:  
Medical: 1-800-498-5743 (U.S. and Canada) or 1-651-523-0318 (international)  
Spill/CHEMTREC: 1-800-424-9300 (U.S. and Canada) or 1-703-527-3887 (international)

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Full text of H statements : see section 16		

#### 2.2. GHS label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hazard statements (GHS CA)	: H222 - Extremely flammable aerosol H229 - Pressurized container; may burst if heated H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness
Precautionary statements (GHS CA)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing dust, fume, gas, mist, vapors, spray. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor. P302+P352 - IF ON SKIN: Wash with plenty of water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER or a doctor if you feel unwell. P321 - Specific treatment (see supplemental first aid instruction on this label). P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: Get medical advice or attention. P337+P313 - If eye irritation persists: Get medical advice or attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Acetone	acetone, propan-2-one, propanone 2-Propanone / acetone / acetone NF / acetone oil / AI3-01238 / Caswell No.004 / chevron acetone / dimethyl formaldehyde / dimethyl ketone / dimethylketal / DMK (=dimethyl ketone) / FEMA No 3326 / ketone propane / KTI acetone / methyl acetyl / propan-2-one / propanone / pyroacetic acid / pyroacetic ether / pyroacetic spirit / STEC 4908105	CAS-No.: 67-64-1	15 – 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Heptane	heptane, n-heptane alkane C7 / ASTM normal-heptane knock test reference fuel / dipropylmethane / dipropylmethane (=normal-heptane) / ESSO heptane / gettysolve-C / heptane / heptane, anhydrous / heptyl hydride / hexylmethane / HYDROSOL-HEPTANE / methylhexane / n-dipropylmethane / n-heptane / n-heptyl hydride / normal-dipropylmethane / normal-heptane / normal-heptyl hydride / NORPAR 7 / protein sequencer reagent S1 / SBP 94/99 / skellysolve C / solvent heptane	CAS-No.: 142-82-5	15 – 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Distillates (petroleum), hydrotreated light	Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	5 – 10	Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Stoddard solvent	Stoddard solvent, Low boiling point naphtha - unspecified, [A colorless, refined petroleum distillate that is free from rancid or objectionable odors and that boils in a range of approximately 148.8°C to 204.4°C. (300°F to 400°F).]	CAS-No.: 8052-41-3	1 – 5	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 4 First-aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
First-aid measures general	: Call a physician immediately.
Personal protection for first-aid responders.	: First-aiders should consider self-protection and use the recommended personal protective equipment (see section 8).

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. Risk of lung edema.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

### SECTION 5 Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media	: DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. Dry chemical, CO <sub>2</sub> , or water spray or regular foam. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Pressurized container: may burst if heated. Heating may cause a fire or explosion.
Explosion hazard	: Explosion risk in case of fire. Heating may cause an explosion.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Special protective actions for fire-fighters

Firefighting instructions	: Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.
Precautionary measures fire	: Keep container tightly closed and away from heat, sparks and flame.

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
Personal Precautions, Protective Equipment and Emergency Procedures	: Self-contained breathing apparatus.
Environmental precautions	: Avoid release to the environment. Avoid discharge to atmosphere.

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 6.2. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Dispose of materials or solid residues at an authorized site.
- For further information refer to section 13.

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Prevent the build-up of electrostatic charge. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Use only non-sparking tools. Ground/bond container and receiving equipment.
- Storage conditions : Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container closed when not in use. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Keep container tightly closed.
- Packaging materials : Always store product in container of same material as original container.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

Acetone (67-64-1)	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	1200 mg/m <sup>3</sup>
	500 ppm
OEL STEL	1800 mg/m <sup>3</sup>
	750 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Acetone
VECD (OEL STEV)	500 ppm
VEMP (OEL TWAEV)	250 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	250 ppm
OEL STEL	500 ppm

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	594 mg/m <sup>3</sup>
	250 ppm
OEL STEL	1187 mg/m <sup>3</sup>
	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	250 ppm
OEL STEL	500 ppm
Notations and remarks	eye irr; CNS impair; BEI
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	594 mg/m <sup>3</sup>
	250 ppm
OEL STEL	1187 mg/m <sup>3</sup>
	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	594 mg/m <sup>3</sup>
	250 ppm
OEL STEL	1187 mg/m <sup>3</sup>
	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWAEV	250 ppm 500 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	594 mg/m <sup>3</sup> 250 ppm
OEL STEL	1187 mg/m <sup>3</sup> 500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Stoddard solvent (8052-41-3)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	572 mg/m <sup>3</sup> 100 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent (Petroleum distillates)
VEMP (OEL TWAEV)	525 mg/m <sup>3</sup> 100 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Stoddard solvent (8052-41-3)</b>	
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent (mineral spirits)
OEL TWA	290 mg/m <sup>3</sup>
OEL STEL	580 mg/m <sup>3</sup>
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	525 mg/m <sup>3</sup> 100 ppm
Notations and remarks	TLV® Basis: Eye, Kidney & Skin dam; Nausea; CNS impair
Regulatory reference	ACGIH 2025
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
Notations and remarks	Eye, skin, & kidney dam;
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	525 mg/m <sup>3</sup> 100 ppm
Notations and remarks	TLV® Basis: Eye, Kidney & Skin dam; Nausea; CNS impair
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	525 mg/m <sup>3</sup> 100 ppm
Notations and remarks	TLV® Basis: Eye, Kidney & Skin dam; Nausea; CNS impair
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Stoddard solvent (8052-41-3)</b>	
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWAEV	100 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	525 mg/m <sup>3</sup> 100 ppm
Notations and remarks	TLV® Basis: Eye, Kidney & Skin dam; Nausea; CNS impair
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Heptane (142-82-5)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Heptane, all isomers
OEL TWA	1640 mg/m <sup>3</sup> 400 ppm
OEL STEL	2050 mg/m <sup>3</sup> 500 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Heptane (all isomers)
VECD (OEL STEV)	500 ppm
VEMP (OEL TWAEV)	400 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Heptane, Isomers
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Heptane, isomers (n-Heptane)
OEL TWA	200 ppm

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Heptane (142-82-5)</b>	
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
Local name	Heptane, all isomers
OEL TWA	400 ppm
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Heptane, isomers (n-Heptane)
OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Heptane, isomers (n-Heptane)
OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Heptane (n-Heptane)
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Heptane (n-Heptane)
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Heptane, All isomers
OEL TWAEV	400 ppm 500 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Heptane, isomers (n-Heptane)
OEL TWA	200 ppm

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Heptane (142-82-5)	
OEL STEL	400 ppm
Notations and remarks	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Heptane (n-Heptane)
OEL TWA	400 ppm
OEL STEL	500 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Appearance : Aerosol.  
Color : Orange  
Odor : Strong  
Odor threshold : No data available  
pH : No data available

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 104 °F
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable aerosol
Vapor pressure	: 5.08 atm
Relative vapor density at 20°C	: No data available
Relative density	: 0.88
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: Lower explosion limit: 1.2 vol % Upper explosion limit: 9.5 vol %
Particle characteristics	: No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Combustible materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

## SECTION 11 Toxicological information

### 11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Ideal® Prima® Spray-On Glo-Fluorescent Orange

Unknown acute toxicity (GHS CA)	5% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 45% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
---------------------------------	---

#### Acetone (67-64-1)

LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 oral	6667 mg/kg
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat	132 mg/l (3 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapors)	76 mg/l Source: ECHA

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
ATE CA (oral)	5800 mg/kg body weight
ATE CA (Dermal)	20000 mg/kg body weight
ATE CA (vapors)	76 mg/l/4h
ATE CA (dust,mist)	132 mg/l/4h
<b>Stoddard solvent (8052-41-3)</b>	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 3000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
ATE CA (oral)	5000 mg/kg body weight
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 oral	15000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID
ATE CA (oral)	15000 mg/kg body weight
<b>Heptane (142-82-5)</b>	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LD50 dermal	3000 mg/kg
LC50 Inhalation - Rat	> 29.29 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), > 4 day(s))
ATE CA (oral)	5000 mg/kg body weight
ATE CA (Dermal)	3000 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
<b>Acetone (67-64-1)</b>	
pH	5 – 6 (20 °C)
<b>Heptane (142-82-5)</b>	
pH	No data available in the literature
Serious eye damage/irritation	: Causes serious eye irritation.
<b>Acetone (67-64-1)</b>	
pH	5 – 6 (20 °C)

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Heptane (142-82-5)</b>	
pH	No data available in the literature
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
<b>Acetone (67-64-1)</b>	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
STOT-single exposure	: May cause drowsiness or dizziness.
<b>Acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Heptane (142-82-5)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
<b>Acetone (67-64-1)</b>	
NOAEL (oral,rat,90 days)	900 mg/kg bw/day
<b>Stoddard solvent (8052-41-3)</b>	
NOAEL (oral,rat,90 days)	1056 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (oral,rat,90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
<b>Heptane (142-82-5)</b>	
LOAEC (inhalation,rat,vapor,90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation,rat,vapor,90 days)	3.3 mg/l air Animal: rat, Animal sex: male
Aspiration hazard	: May be fatal if swallowed and enters airways.
<b>Acetone (67-64-1)</b>	
Viscosity, kinematic	No data available in the literature
<b>Stoddard solvent (8052-41-3)</b>	
Viscosity, kinematic	0.9 – 1.6 mm <sup>2</sup> /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
<b>Heptane (142-82-5)</b>	
Viscosity, kinematic	0.641 mm <sup>2</sup> /s (20 °C, EN ISO 3104: Capillary viscometer)
Symptoms/effects	: May cause drowsiness or dizziness.

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. Risk of lung edema.

## SECTION 12 Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
EC50 - Crustacea [1]	12600 – 12700 mg/l
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Stoddard solvent (8052-41-3)	
LC50 - Fish [1]	2.5 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	0.42 mg/l
EC50 96h - Algae [1]	0.58 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Distillates (petroleum), hydrotreated light (64742-47-8)	
LC50 - Fish [1]	2.2 mg/l

Heptane (142-82-5)	
LC50 - Fish [1]	5.738 mg/l Source: QSAR
EC50 - Crustacea [1]	1.5 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.3 mg/l (Pseudokirchneriella subcapitata, Fresh water, QSAR, Biomass)
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

Ideal® Prima® Spray-On Glo-Fluorescent Orange	
Persistence and degradability	Not rapidly degradable
Acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
<b>Stoddard solvent (8052-41-3)</b>	
Persistence and degradability	Not rapidly degradable
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
Persistence and degradability	Not rapidly degradable
<b>Heptane (142-82-5)</b>	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.92 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.06 g O <sub>2</sub> /g substance
ThOD	3.52 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>Acetone (67-64-1)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Partition coefficient n-octanol/water (Log Kow)	-0.23
<b>Stoddard solvent (8052-41-3)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.16 – 7.06 Source: ICSC
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
<b>Heptane (142-82-5)</b>	
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
BCF - Other aquatic organisms [1]	552 (BCFBAF v3.00, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	4.5 (Literature)

### 12.4. Mobility in soil

<b>Acetone (67-64-1)</b>	
Surface tension	23.3 mN/m (20 °C)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
<b>Heptane (142-82-5)</b>	
Surface tension	19.66 mN/m (25 °C)
Ecology - soil	Low potential for adsorption in soil.

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### Heptane (142-82-5)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.4 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	--

### 12.5. Other adverse effects





Ozone	: Not classified
Fluorinated greenhouse gases	: No

## SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

## SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
<b>14.1. UN Number</b>			
UN1950	UN1950	1950	1950
<b>14.2. UN Proper Shipping Name</b>			
AEROSOLS	Aerosols, flammable, n.o.s.	AEROSOLS	Aerosols, flammable
<b>Transport document description</b>			
UN1950 AEROSOLS, 2.1	UN1950 Aerosols, flammable, n.o.s., 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
<b>14.3. Transport hazard class(es)</b>			
2.1	2.1	2.1	2.1
			
<b>14.4. Packing group, if applicable</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 14.6. Special precautions for user

#### TDG

UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

#### DOT

UN-No. (DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### IMDG

Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### IATA

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78<sup>9</sup> and the IBC Code<sup>10</sup>

Not applicable

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 15 Regulatory information

#### Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

#### Stoddard solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List)

#### Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Heptane (142-82-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Stoddard solvent (8052-41-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Heptane (142-82-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### SECTION 16 Other Information

Issue date : 12-17-2025

Revision date : 12-18-2025

Supersedes : 12-17-2025

#### Full text of hazard classes and H-statements:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H229	Pressurized container; may burst if heated
H304	May be fatal if swallowed and enters airways

# Ideal® Prima® Spray-On Glo-Fluorescent Orange

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Full text of hazard classes and H-statements:	
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects.
H350	May cause cancer.
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.