

SECTION 1 Identification

1.1. GHS Product identifier

Product form : Mixture
Trade name : Ideal® Prima Marc™ Paint-Red
Type of product : Animal Safety -- [Animal Safety]
Product code : 341280

1.2. Other means of identification

Part Number(s) : 341280

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Animal marking ink
Restrictions on use : For animal use only

1.4. Supplier's details

Supplier

Neogen Corporation
620 Leshar Place
Lansing, Michigan 48912
United States of America
T 800.234.5333
sds@neogen.com - <https://www.neogen.com/>

1.5. Emergency phone number

Emergency number : 24 hours:
Medical: 1-800-498-5743 (U.S. and Canada) or 1-651-523-0318 (international)
Spill/CHEMTREC: 1-800-424-9300 (U.S. and Canada) or 1-703-527-3887 (international)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.

Full text of H statements : see section 16

2.2. GHS label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :  

Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : H222 - Extremely flammable aerosol
H229 - Pressurized container; may burst if heated

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS CA)

H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or a doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Ethanol	ethanol, ethyl alcohol	CAS-No.: 64-17-5	30 – 60	Flam. Liq. 1, H224 Carc. 1A, H350

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Isopropanol	2-Propanol 1-methylethanol / 1-methylethyl alcohol / 2- hydroxypropane / 2-Propanol / 2- propanol, anhydro us / 2-propyl alcohol / A13- 01636 / alcojel / alcosolve / AVANTIN / AVANTINE / caswell No 507 / chromar (=2- propanol) / combi- schutz / CORONA WIRE CLEANER (=2-propanol) / CTL R-53 reducer / dimethyl carbinol / DISK DRIVE HEAD CLEANING KIT (=2-propanol) / ethyl carbinol / hartosol / hydroxypropane / imsol A / IPA SGL / IPA T1 / IPA USP / IPA, anhydrous / IPA- EG / isoethylcarbinol / isohol / isopropanol / isopropanol, anhydrous / isopropyl alcohol / isopropyl alcohol, anhydrous / KENCO #880-T FLUX THINNER (=2-propanol) / LENS CLENS #3 (=2-propanol) / lutosol / normal- propan-2-ol / n- propan-2-ol / perspirit / persprit / petrohol / PRO / propan-2-ol / propyl alcohol (=sec-propyl alcohol) / pseudo- propyl alcohol / secondary-propyl	CAS-No.: 67-63-0	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
-------------	---	------------------	---------	---

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
	alcohol / sec-propanol / sec-propyl alcohol / spectrar / STCC 4904205 / sterisol hand disinfectant / takineocol / TEXPADS / visco 1152 / XEROX FILM REMOVER			

Full text of hazard classes and H-statements : see section 16

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First-aiders should consider self-protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. Dry chemical, CO ₂ , or water spray or regular foam. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Pressurized container: may burst if heated. Heating may cause a fire or explosion.
Explosion hazard	: Explosion risk in case of fire. Heating may cause an explosion.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

5.3. Special protective actions for fire-fighters

- Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.
- Precautionary measures fire : Keep container tightly closed and away from heat, sparks and flame.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
- Personal Precautions, Protective Equipment and Emergency Procedures : Self-contained breathing apparatus.
- Environmental precautions : Avoid release to the environment. Avoid discharge to atmosphere.

6.2. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Dispose of materials or solid residues at an authorized site.
- For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Prevent the build-up of electrostatic charge. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Use only non-sparking tools. Ground/bond container and receiving equipment.
- Storage conditions : Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container closed when not in use. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Keep container tightly closed.
- Storage temperature : ≤ 122 °F
- Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Ethanol (Ethyl alcohol)
OEL TWA	1880 mg/m ³
	1000 ppm

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Ethanol (64-17-5)	
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
VECD (OEL STEV)	1000 ppm
Notations and remarks	C3
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1000 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1880 mg/m ³ 1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1000 ppm
Notations and remarks	URT irr
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1880 mg/m ³ 1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1880 mg/m ³ 1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Ethanol
OEL TWA	1000 ppm

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Ethanol (64-17-5)	
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Ethanol
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Ethanol
OEL TWAEV	1000 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Ethanol
OEL STEL	1880 mg/m ³ 1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Ethanol
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Isopropanol (67-63-0)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	2-Propanol (Isopropyl alcohol, isopropanol)
OEL TWA	492 mg/m ³ 200 ppm
OEL STEL	984 mg/m ³ 400 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Isopropyl alcohol
VECD (OEL STEV)	400 ppm
VEMP (OEL TWAEV)	200 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Isopropanol (67-63-0)	
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Isopropanol (Isopropyl alcohol, 2-Propanol)
OEL TWA	200 ppm
OEL STEL	400 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	2-Propanol
OEL TWA	491 mg/m ³ 200 ppm
OEL STEL	984 mg/m ³ 400 ppm
Notations and remarks	TLV® Basis: Eye & URT irr; CNS repair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	2-Propanol
OEL TWA	200 ppm
OEL STEL	400 ppm
Notations and remarks	Eye & URT irr; CNS impair
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	2-Propanol
OEL TWA	491 mg/m ³ 200 ppm
OEL STEL	984 mg/m ³ 400 ppm
Notations and remarks	TLV® Basis: Eye & URT irr; CNS repair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	2-Propanol
OEL TWA	491 mg/m ³ 200 ppm
OEL STEL	984 mg/m ³ 400 ppm
Notations and remarks	TLV® Basis: Eye & URT irr; CNS repair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Isopropanol (67-63-0)	
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OEL TWA	200 ppm
OEL STEL	400 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OEL TWA	200 ppm
OEL STEL	400 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	2-Propanol
OEL TWAEV	200 ppm 400 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	2-Propanol
OEL TWA	491 mg/m ³ 200 ppm
OEL STEL	984 mg/m ³ 400 ppm
Notations and remarks	TLV® Basis: Eye & URT irr; CNS repair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OEL TWA	200 ppm
OEL STEL	400 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: Red
Odor	: Alcohol
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable aerosol
Vapor pressure	: 5.08 atm
Relative vapor density at 20°C	: No data available
Relative density	: 0.88
Solubility	: not soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: Lower explosion limit: 1.8 vol %
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Combustible materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Ideal® Prima Marc™ Paint-Red	
Unknown acute toxicity (GHS CA)	60% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg (Rat, male and female) (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg rabbit, OECD Test Guideline 402
LC50 Inhalation - Rat	51 mg/l (Rat; 4 h; vapour) (OECD Test Guideline 403)
ATE CA (oral)	10470 mg/kg body weight
ATE CA (vapors)	51 mg/l/4h
ATE CA (dust,mist)	51 mg/l/4h

Isopropanol (67-63-0)	
LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 oral	4384 mg/kg
LD50 dermal rabbit	13120 mg/kg bw/day (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Converted value, Dermal, 14 day(s))
LD50 dermal	12870 mg/kg
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE CA (oral)	4384 mg/kg body weight
ATE CA (Dermal)	12870 mg/kg body weight

Skin corrosion/irritation : Not classified

Isopropanol (67-63-0)	
pH	No data available in the literature

Serious eye damage/irritation : Causes serious eye irritation.

Isopropanol (67-63-0)	
pH	No data available in the literature

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified.

Ethanol (64-17-5)	
NOAEL (chronic,oral,animal/male,2 years)	> 4250 mg/kg body weight (Mouse, male)(Target Organs: Liver)(Oral; 105 weeks; Frequency of treatment: 5 days/week)(OPPTS 870.4200)
NOAEL (chronic,oral,animal/female,2 years)	> 4000 mg/kg body weight (Mouse, female)(Target Organs: Liver)(Oral; 105 weeks; Frequency of treatment: 5 days/week)
IARC group	1 - Carcinogenic to humans

Isopropanol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

Ethanol (64-17-5)	
NOAEL (animal/male, F1)	13.8 (Mouse, male and female)(OECD Test Guideline 416)Reduction in sperm motility.
NOAEL (animal/female, F1)	13.8 (Mouse, male and female)(OECD Test Guideline 416)Reduction in sperm motility.

STOT-single exposure : May cause drowsiness or dizziness.

Isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Ethanol (64-17-5)	
LOAEL (oral, rat, 90 days)	3160 mg/kg bodyweight/day
NOAEL (oral, rat, 28 days)	1730 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	3160 mg/kg bodyweight/day

Aspiration hazard : Not classified

Isopropanol (67-63-0)	
Viscosity, kinematic	2.66 mm ² /s (25 °C, Estimated value)

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion : May cause irritation to the digestive tract.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Isopropanol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Isopropanol (67-63-0)	
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1000 mg/l
ErC50 algae	1000 mg/l
NOEC chronic crustacea	100 mg/l

12.2. Persistence and degradability

Ideal® Prima Marc™ Paint-Red	
Persistence and degradability	Not rapidly degradable

Ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.

Isopropanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.2 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)

12.4. Mobility in soil

Isopropanol (67-63-0)	
Surface tension	No data available in the literature
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.19 – 0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

Ideal® Prima Marc™ Paint-Red





Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
UN1950	UN1950	1950	1950
14.2. UN Proper Shipping Name			
AEROSOLS	Aerosols, flammable, n.o.s.	AEROSOLS	Aerosols, flammable
Transport document description			
UN1950 AEROSOLS, 2.1	UN1950 Aerosols, flammable, n.o.s., 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

TDG

UN-No. (TDG)

: UN1950

TDG Special Provisions

: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index

: 1 L

Excepted quantities (TDG)

: E0

Passenger Carrying Road Vehicle or Passenger

: 75 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number

: 126

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

DOT	
UN-No. (DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG	
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA	
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

Isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Canada DSL & NDSL Flags	Significant New Activity (SNAc) provisions of the Act apply
-------------------------	---

Ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Ideal® Prima Marc™ Paint-Red

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Isopropanol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16 Other Information

Issue date : 12-16-2025

Full text of hazard classes and H-statements:

H222	Extremely flammable aerosol
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H229	Pressurized container; may burst if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer.

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.