

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : Ideal® Prima Marc™ Paint-Blue  
Product code : 341297

#### 1.2. Other means of identification

Part Number(s) : 341297

#### 1.3. Recommended use of the chemical and restrictions on use

Restrictions on use : For animal use only

#### 1.4. Details of manufacturer or importer

##### Supplier

Neogen Corporation  
620 Leshler Place  
Lansing Michigan 48912  
United States of America  
T 800.234.5333  
[sds@neogen.com](mailto:sds@neogen.com) - <https://www.neogen.com/>

##### Importer

Neogen Australasia Pty Ltd  
14 Hume Drive  
Bundamba Queensland 4304  
Australia  
T 07 3736 2134  
[naa@neogen.com](mailto:naa@neogen.com) - <https://www.neogen.com/>

#### 1.5. Emergency phone number

Emergency number : 24 hours:  
Medical: 1-800-498-5743 (U.S. and Canada) or 1-651-523-0318 (international)  
Spill/CHEMTREC: 1-800-424-9300 (U.S. and Canada) or 1-703-527-3887 (international)

Country/Area	Organisation	Emergency number
Australia	NSW Poisons Information Centre. The Children's Hospital at Westmead. Locked Bag 4001 NSW 2145 Westmead.	13 11 26

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1 H222;H229  
Acute toxicity (dermal), Category 5 H313  
Serious eye damage/eye irritation, Category 2A H319  
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Signal word (GHS AU) :

Danger

Contains :

Ethanol (30 – 60 %); Isopropanol (10 – 30 %)

Hazard statements (GHS AU) :

H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H313 - May be harmful in contact with skin

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

Precautionary statements (GHS AU)

- H319 - Causes serious eye irritation
- H336 - May cause drowsiness or dizziness
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 - Do not pierce or burn, even after use.
- P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 - Call a POISON CENTER or doctor if you feel unwell.
- P337+P313 - If eye irritation persists: Get medical advice/attention.
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
- P405 - Store locked up.
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- : 30% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Unknown acute toxicity (GHS AU)

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Ethanol	64-17-5	30 – 60	Flam. Liq. 1, H224 Acute Tox. 5 (Dermal), H313 Carc. 1A, H350
Isopropanol	67-63-0	10 – 30	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Eye Irrit. 2A, H319 STOT SE 3, H336
Other substances (not contributing to the classification of this product)	-	10 – 60	-

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
- Self protection of the first-aiders : First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

### 4.2. Symptoms caused by exposure

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after inhalation : None under normal conditions.
- Symptoms/effects after skin contact : May be harmful in contact with skin.

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

Symptoms/effects after eye contact : Eye irritation.  
Symptoms/effects after ingestion : None under normal conditions.

### 4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.  
Absorb spillage to prevent material damage.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.  
Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.  
Methods for cleaning up : Mechanically recover the product.

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
- Storage temperature : ≤ 122 °F
- Packaging materials : Always store product in container of same material as original container.

### SECTION 8: Exposure controls and personal protection

#### 8.1. Control parameters - exposure standards

##### Ethanol (64-17-5)

###### Australia - Occupational Exposure Limits

Local name	Ethyl alcohol (Ethanol)
OES TWA	1880 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)

##### Isopropanol (67-63-0)

###### Australia - Occupational Exposure Limits

Local name	Isopropyl alcohol (Propan-2-ol)
OES TWA	983 mg/m <sup>3</sup>
	400 ppm
OES STEL	1230 mg/m <sup>3</sup>
	500 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2024)

#### 8.2. Monitoring methods

No additional information available

#### 8.3. Engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

#### 8.4. Individual protection measures, such as personal protective equipment (PPE)

- Personal protective equipment : Wear recommended personal protective equipment.
- Hand protection : Protective gloves
- Eye protection : Safety glasses
- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

### Personal protective equipment symbol(s)



Environmental exposure controls

: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Blue
Odour	: Alcohol
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not applicable
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: Vapour pressure: 5.08 atm
Relative density	: No data available
Density	: Relative density: 0.88
Solubility	: not soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: 1.8 vol %
Minimum ignition energy	: No data available
Fat solubility	: No data available

## SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: May be harmful in contact with skin.
Acute toxicity (inhalation)	: Not classified

Ideal® Prima Marc™ Paint-Blue	
ATE AU (dermal)	4166.667 mg/kg bodyweight
Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg (Rat, male and female) (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg rabbit, OECD Test Guideline 402
LC50 Inhalation - Rat	51 mg/l (Rat; 4 h; vapour) (OECD Test Guideline 403)

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

Isopropanol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 oral	4384 mg/kg
LD50 dermal rabbit	13120 mg/kg bw/day (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Converted value, Dermal, 14 day(s))
LD50 dermal	12870 mg/kg
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Unknown acute toxicity (GHS AU) : 30% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified.

Ethanol (64-17-5)	
NOAEL (chronic, oral, animal/male, 2 years)	> 4250 mg/kg bodyweight (Mouse, male)(Target Organs: Liver)(Oral; 105 weeks; Frequency of treatment: 5 days/week)(OPPTS 870.4200)
NOAEL (chronic, oral, animal/female, 2 years)	> 4000 mg/kg bodyweight (Mouse, female)(Target Organs: Liver)(Oral; 105 weeks; Frequency of treatment: 5 days/week)
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified

Ethanol (64-17-5)	
NOAEL (animal/male, F1)	13.8 (Mouse, male and female)(OECD Test Guideline 416)Reduction in sperm motility.
NOAEL (animal/female, F1)	13.8 (Mouse, male and female)(OECD Test Guideline 416)Reduction in sperm motility.

STOT-single exposure : May cause drowsiness or dizziness.

Isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Ethanol (64-17-5)	
LOAEL (oral, rat, 90 days)	3160 mg/kg bodyweight/day
NOAEL (oral, rat, 28 days)	1730 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	3160 mg/kg bodyweight/day

Aspiration hazard : Not classified

Isopropanol (67-63-0)	
Viscosity, kinematic	2.66 mm <sup>2</sup> /s (25 °C, Estimated value)

## SECTION 12: Ecological information

### 12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

Ethanol (64-17-5)	
LD50 dermal rabbit	> 2000 mg/kg rabbit, OECD Test Guideline 402
LD50 oral rat	10470 mg/kg (Rat, male and female) (OECD Test Guideline 401)
Isopropanol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1000 mg/l
ErC50 algae	1000 mg/l
NOEC chronic crustacea	100 mg/l
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.19 – 0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
LD50 dermal rabbit	13120 mg/kg bw/day (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Converted value, Dermal, 14 day(s))
LD50 oral rat	5840 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))

### 12.2. Persistence and degradability

Ideal® Prima Marc™ Paint-Blue	
Persistence and degradability	Not rapidly degradable
Ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.
Isopropanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.2 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.2 g O <sub>2</sub> /g substance
ThOD	2.4 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.19 – 0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

Isopropanol (67-63-0)	
Surface tension	No data available in the literature
Ecology - soil	Highly mobile in soil.
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.19 – 0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

#### Ideal® Prima Marc™ Paint-Blue




Fluorinated greenhouse gases	False
------------------------------	-------

## SECTION 13: Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.  
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

## SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
<b>14.1. UN number</b>		
1950	1950	1950
<b>14.2. UN Proper Shipping Name</b>		
AEROSOLS	AEROSOLS	Aerosols, flammable
<b>Transport document description</b>		
Not applicable	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344, 381  
Limited quantities (ADG) : 1I

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

Excepted quantities (ADG) : E0  
Packing instructions (ADG) : P207, LP200  
Special packing provisions (ADG) : PP87, L2

### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Limited quantities (IMDG) : SP277  
Excepted quantities (IMDG) : E0  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

### Air transport

UN-No. (IATA) : 1950  
PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

## 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : All the chemicals contained in this product are listed introductions Inventory) status

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Not applicable

#### Australian Pesticides and Veterinary Medicines Authority (APVMA)

Not applicable

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Classification	
Aerosol 1	H222;H229
Acute Tox. 5 (Dermal)	H313
Eye Irrit. 2A	H319
STOT SE 3	H336

# Ideal® Prima Marc™ Paint-Blue

## Safety Data Sheet

according to the WHS Regulations

Full text of H-statements	
Acute Tox. 5 (Dermal)	Acute toxicity (dermal), Category 5
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Aerosol 1	Aerosol, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H224	Extremely flammable liquid and vapour
H225	Highly flammable liquid and vapour
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.