

## Prima Marc Blue Marking Dye

### SECTION 1 - IDENTIFICATION

**Product Identifier**

Product Number(s) N7460CT  
 Product Name Prima Marc Blue Marking Dye - Metered Tip

Other Means of Identification None

**Recommended Use and Restrictions on Use**

Recommended Use Livestock marking dye.  
 Restrictions on Use None Identified

Emergency Phone Number
Emergency Telephone: Chemtrec: 1 (800) 424-9300 Outside USA and Canada: +1 (703) 527-3887

**MANUFACTURER DETAILS**

Name Manufactured for Neogen Corporation  
 Address 944 Nandino Blvd.  
 Lexington, KY 40511  
 Phone Number 800-621-8829  
 Fax Number 859-254-8722  
 Email inform@neogen.com

### SECTION 2 - IDENTIFICATION

**Hazard Classification**

HEALTH HAZARDS				PHYSICAL HAZARDS					
Acute Tox. Oral	<input type="checkbox"/> 4	Mutagenicity	<input type="checkbox"/>	Unstable Explosive	<input type="checkbox"/>	Refrigerated Liq. Gas	<input type="checkbox"/>	Pyrophoric Solid	<input type="checkbox"/>
Acute Tox. Skin	<input type="checkbox"/>	Carcinogenicity	<input type="checkbox"/>	Explosive	<input type="checkbox"/>	Flammable Liquid	<input type="checkbox"/>	Emits Flammable Gas	<input type="checkbox"/>
Acute Tox. Inhalation	<input type="checkbox"/>	Tox. to Reproduction	<input type="checkbox"/>	Flammable Gas	<input type="checkbox"/>	Flammable Solid	<input type="checkbox"/>	Oxidizing Liquid	<input type="checkbox"/>
Skin Irritation	<input type="checkbox"/>	STOT SE	<input type="checkbox"/> 1	Aerosol	<input type="checkbox"/> 1	Self-Reactive Sub.	<input type="checkbox"/>	Oxidizing Solid	<input type="checkbox"/>
Eye Irritation	<input type="checkbox"/>	STOT RE	<input type="checkbox"/>	Oxidizing Gas	<input type="checkbox"/>	Pyrophoric Liquid	<input type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>
Resp. Sensitization	<input type="checkbox"/>	Aspiration Hazard	<input type="checkbox"/>	Gas Under Pressure	<input type="checkbox"/> X	Self-Heating Substance	<input type="checkbox"/>	Corrosive to Metal	<input type="checkbox"/>
Skin Sensitization	<input type="checkbox"/>		<input type="checkbox"/>	<b>ENVIRONMENTAL HAZARDS (GHS Rev 3 Only)</b>					
	<input type="checkbox"/>		<input type="checkbox"/>	Aquatic Acute	<input type="checkbox"/>	Aquatic Chronic	<input type="checkbox"/>	Ozone Depleting	<input type="checkbox"/>

Signal Word

Danger

Hazard Pictograms



Hazard Statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes damage to organs.

Precautionary Statements

**General** Keep out of reach of children.  
**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Wash hands thoroughly after handling. Do not eat, drink, or smoke when using this product.  
**Response** IF exposed: Call a doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor if you feel unwell. Rinse mouth.  
**Storage** Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



# SAFETY DATA SHEET

Part No. N7460CT Aerosol

January 4, 2019

Revision 2

Page 2 of 7

## Prima Marc Blue Marking Dye

**Disposal** *Dispose of contents/container in accordance with local regulations.*

**Hazards Not Otherwise Classified** *None identified.*

**Unknown Acute Toxicity** *3.2 % by wt*

### SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

ID	INGREDIENT	CAS NUMBER	% WT RANGE*
1	Liquefied Petroleum Gas	0068476-86-8	40 - 70
2	Ethanol	0000064-17-5	15 - 40
3	Methanol	0000067-56-1	1 - 5
4	Acetone	0000067-64-1	1 - 5
5	Ethyl Acetate	0000141-78-6	1 - 5
6	Butyl Cellosolve	0000111-76-2	0.5 - 1.5

\* Exact percentages of composition withheld as trade secret

### SECTION 4 - FIRST AID MEASURES

#### Description of First-Aid Measures

**General** *If exposed or concerned seek medical advice/attention.*

**Eye Contact** *Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.*

**Skin Contact** *Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.*

**Ingestion** *Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.*

**Inhalation** *Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.*

**First-Aid Responder Protection** *Wear adequate personal protective equipment based on the nature and severity of the emergency.*

#### Most Important Symptoms and Effects, Both Acute and Delayed

**Eye Contact** *Liquid contact may cause pain along with moderate eye irritation.*

**Skin Contact** *Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.*

**Ingestion** *Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.*

**Inhalation** *Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.*

#### Indication of Immediate Medical Attention and Special Treatment

**Notes to Physician** *Treat symptomatically.*

**Specific Treatments/Antidotes** *No information available.*

**Immediate Medical Attention** *No information available.*

### SECTION 5 - FIRE-FIGHTING MEASURES

#### Extinguishing Media

**Suitable Extinguishing Media** *Water, CO<sub>2</sub>, dry chemical, or universal aqueous film forming foam*

**Unsuitable Extinguishing Media** *Water jet*

#### Specific Hazards Arising from the Chemical or Mixture

**Decomposition Products** *Oxides of carbon (CO, CO<sub>2</sub>), smoke, and/or vapors*



# SAFETY DATA SHEET

Part No. N7460CT Aerosol

January 4, 2019

Revision 2

Page 3 of 7

## Prima Marc Blue Marking Dye

### Hazards from the Product

*CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. In a fire or if heated, a pressure increase will occur which may result in the container bursting. Vapours heavier than air may spread along the ground and travel to an ignition source.*

### Advice for Firefighters

#### Protective Actions

*Use water spray to cool fire exposed containers as contents may rupture violently from heat developed pressure.*

#### Protective Equipment

*As with any fire wear SCBA pressure-demand, MSHA/NIOSH approved, and full protective gear.*

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

#### For Non-Emergency Personnel

*No action should be taken by non-emergency personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.*

#### For Emergency Responders

*Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel.*

### Environmental Precautions

#### Precautions

*Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.*

### Methods and Materials for Containment and Cleaning Up

#### Containment Procedures

*Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents. DO NOT use combustible material such as sawdust.*

#### Cleanup Procedures

*Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.*

#### Other Information

*Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.*

#### Prohibited Materials

*Combustible absorbent material such as sawdust, use of equipment that may cause sparking.*

## SECTION 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

#### General Handling Precautions

*KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Wash hands after use.*

#### Hygiene Recommendations

*Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.*

### Conditions for Safe Storage Including Any Incompatibilities

#### Storage Requirements

*Storage of individual cans should be done in an area below 50 °C (122 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 3 Aerosol.*

#### Incompatibilities

*Segregate storage away from materials indicated in Section 10*

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control Parameters

#### Occupational Exposure Limits

ID	OSHA			NIOSH			ACGIH			AIHA	
	PEL	STEL	CEILING	IDLH	REL	STEL	CEILING	TLV	STEL		CEILING
1	1000 ppm	–	–	2000 ppm	1000 ppm	–	–	1000 ppm	–	–	–
2	–	–	–	3300 ppm	1000 ppm	–	–	1000 ppm	–	–	–
3	200 ppm	–	–	6000 ppm	200 ppm	250 ppm	–	200 ppm	250 ppm	–	–



# SAFETY DATA SHEET

Part No. N7460CT Aerosol

January 4, 2019

Revision 2

Page 4 of 7

## Prima Marc Blue Marking Dye

ID	PEL	OSHA		IDLH	NIOSH			TLV	ACGIH		AIHA WEEL
		STEL	CEILING		REL	STEL	CEILING		STEL	CEILING	
4	1000 ppm	–	–	2500 ppm	250 ppm	–	–	250 ppm	500 ppm	–	–
5	400 ppm	–	–	2000 ppm	400 ppm	–	–	400 ppm	–	–	–
6	50 ppm	–	–	700 ppm	5 ppm	–	–	20 ppm	–	–	–

### Biological Exposure Indices

ID	DETERMINANT	SAMPLING TIME	BEI	NOTATION
3	Methanol in urine	End of shift	15 mg/L	B, Ns
4	Acetone in urine	End of shift	50 mg/L	Ns
6	Butoxyacetic acid (BAA) in urine	End of shift	200 mg/g creatinine	–

**Other Control Parameters** Not Available

### Appropriate Engineering Control

**Engineering Measures** Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

### Individual Protection Measures

**Hygiene Considerations** Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.

**Thermal Protection** This product does not present a thermal hazard.

**Respiratory Protection** An approved respirator with organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

**Skin Protection** For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

**Eye/Face Protection** Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

**Other Protective Equipment** Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### Physical Properties

<b>Boiling Point</b>	> 56.1 °C (133.0 °F)	<b>Melting / Freezing Point</b>	> -97.7 °C (-143.0 °F)
<b>Flash Point, Liquid</b>	> -17.0 °C (1.4 °F)	<b>Flash Point, Propellant</b>	-104.4 °C (-156.0 °F)
<b>Explosive Limits</b>	2.50% - 36.00%	<b>Autoignition Temperature, Liquid</b>	385.0 °C (725.0 °F)
<b>Flammability</b>	Extremely Flammable Aerosol	<b>Relative Density (H<sub>2</sub>O = 1)</b>	0.624 g/cc
<b>Molecular Weight</b>	Not Available	<b>Weight</b>	5.206 lbs/gal
<b>Vapor Pressure</b>	70.00 psig	<b>pH</b>	Not Available
<b>Vapor Density</b>	2.000 g/cc Maximum	<b>Evaporation Rate</b>	Not Available
<b>Form</b>	Pressurized Product	<b>Partition Coefficient</b>	Not Available
<b>Viscosity</b>	Not Available	<b>Refractive Index</b>	Not Available
<b>Odor Threshold</b>	Not Available	<b>Heat of Combustion (ΔH<sub>c</sub>)</b>	Not Available
<b>Odor</b>	Paint Like	<b>Water Solubility</b>	Not Available
<b>Appearance / Color</b>	Blue Liquid	<b>Decomposition Temperature</b>	Not Available

### Air Quality Properties

<b>Percent Volatile</b>	97% Wt (96% Vol) Max	<b>VOC Regulatory</b>	5.010 lbs/gal (600.348 g/L)
<b>Percent VOC</b>	95% Wt (94% Vol) Max	<b>VOC Actual</b>	4.918 lbs/gal (589.279 g/L)
<b>Percent HAP</b>	4% Wt (3% Vol) Max	<b>HAP Content</b>	0.168 lbs/gal (20.131 g/L)
<b>Solids/Non Volatile Content</b>	4% Wt (5% Vol) Max	<b>Maximum Incremental Reactivity</b>	1.217 g O <sub>3</sub> /g
<b>Global Warming Potential</b>	4.902		

## Prima Marc Blue Marking Dye

### SECTION 10 - STABILITY AND REACTIVITY

<b>Reactivity</b>	No specific test data related to reactivity is available for this product or its ingredients.
<b>Chemical Stability</b>	This product is stable.
<b>Hazardous Reactions</b>	Under normal conditions of storage and use, hazardous reactions are not expected to occur.
<b>Conditions to Avoid</b>	Keep away from heat, sparks, flame, and red hot metal.
<b>Material Incompatibility</b>	Acids, Activated Carbon, Alkali Metals, Alkalis, Ammonia, Bases, Carbon Tetrachloride, Chlorine Dioxide, Diethyl Zinc, Hexachloromelamine, Hydrogen Peroxide, Isocyanates, Isoprene, Lithium Aluminum Hydride, Mineral Acids, Nitrates, Potassium Tert-Butoxide, Strong Oxidizing Agents, Strong Reducing Agents, Sulfur Dichloride, Trichloromelamine
<b>Decomposition Productions</b>	Oxides of Carbon, Acetic Acid, Formaldehyde fumes, Hydrogen Peroxide, Isopropanol, Methanol, Peroxides may be formed depending on fire conditions.

### SECTION 11 - TOXICOLOGICAL INFORMATION

#### Acute Toxicity Estimates (mixture)

<b>Oral LD<sub>50</sub></b>	1034 mg/kg
<b>Dermal LD<sub>50</sub></b>	12344 mg/kg
<b>Inhalation LC<sub>50</sub></b>	837 mg/L 4-hour

#### Acute Toxicity on Ingredients

ID	ORAL LD50		DERMAL LD50		INHALATION LC50		
	VALUE	SPECIES	VALUE	SPECIES	VALUE	TIME	SPECIES
1	–	–	–	–	658 mg/L	4h	rat
2	7060 mg/kg	rat	>15800 mg/kg	rabbit	>32380 ppm	4h	rat
3	143 mg/kg	human	17100 mg/kg	rabbit	128.2 mg/L	4h	rat
4	5800 mg/kg	rat	20000 mg/kg	rabbit	50100 mg/m3	8h	rat
5	10200 mg/kg	rat	>18000 mg/kg	rabbit	>32380 ppm	4h	rat
6	1400 mg/kg	guinea pig	>2000 mg/kg	guinea pig	2211 mg/m3	4h	rat

#### Health Hazard Classification

<b>Skin Corrosion / Irritation</b>	Classification criteria not met
<b>Eye Damage / Irritation</b>	Classification criteria not met
<b>Respiratory Irritation</b>	Classification criteria not met
<b>Respiratory / Skin Sensitization</b>	Classification criteria not met
<b>Germ Cell Mutagenicity</b>	Classification criteria not met
<b>Reproductive Toxicity</b>	Classification criteria not met
<b>STOT - Single Exposure</b>	Category 1
<b>STOT - Repeated Exposure</b>	Classification criteria not met
<b>Aspiration Hazard</b>	Classification criteria not met

#### Carcinogen Data

ID	Calif Prop-65	OSHA	NIOSH	ACGIH	NTP	IARC
6	–	–	–	A3	–	–

#### Information on the Likely Routes of Exposure

<b>Routes of Exposure</b>	Skin contact, skin absorption, eye contact, inhalation
---------------------------	--

#### Information on Physical, Chemical and Toxicological Effects

<b>Symptoms of Exposure</b>	Asphyxia, Blindness, Central Nervous System Depression, Cough, Dermatitis, Dizziness, Drowsiness, Skin Irritation, Throat Irritation, Upper Respiratory System Irritation, Visual Disturbance, Vomiting
-----------------------------	---

#### Delayed and Immediate Effects and also Chronic Effects from Short and Long-Term Exposure

<b>Delayed Effects</b>	No known delayed effects.
<b>Immediate Effects</b>	No known immediate effects.

## Prima Marc Blue Marking Dye

**Chronic Effects** Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal.

**Medical Conditions Aggravated** May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

**Target Organs** Bladder, Blood, Cardiovascular System, Central Nervous System, Eyes, Liver, Lymphoid System, Respiratory System, Skin

### SECTION 12 - ECOLOGICAL INFORMATION

#### Acute Aquatic Toxicity

ID	TYPE	FISH			INVERTEBRATES			AQUATIC PLANTS			MICROORGANISMS		
		VALUE	PERIOD	TYPE	VALUE	PERIOD	TYPE	VALUE	PERIOD	TYPE	VALUE	PERIOD	
2	LC50	11000 mg/L	96h	EC50	10800 mg/L	24h	LOEC	1450 mg/L	8d	LOEC	6500 mg/L	16h	
3	LC50	15400 mg/L	96h	EC50	>10000 mg/L	48h	EC50	22000 mg/L	96h	EC5	6600 mg/L	16h	
4	LC50	5540 mg/L	96h	LC50	8800 mg/L	48h	NOEC	530 mg/L	8d	EC5	1700 mg/L	16h	
5	LC50	230 mg/L	96h	EC50	717 mg/L	48h	IC50	3300 mg/L	48h	EC10	2900 mg/L	16h	
6	LC50	1474 mg/L	96h	EC50	1550 mg/L	48h	LOEC	900 mg/L	7d	EC5	911 mg/L	48h	

#### Ecological Data

ID	PERSISTENCE AND DEGRADABILITY				BIOACCUMULATIVE POTENTIAL		MOBILITY Koc
	PERSISTENCE	BOD	COD	ThOD	Pow / Kow	BCF	
2	—	930 mg/g / 5d	1700 mg/g	2.1 mg/g	-0.31 log Pow	—	—
3	72% / 5 days	850 mg/g	1420 mg/g	1500 mg/g	-77 log Pow	0.48 log BCF	0.44 log Koc
4	90.9% / 28 days	1.85 mg/g / 5 d	2.07 mg/g	2.21 g/g	-0.24 log Pow	0.69 BCF	1.26 log Koc
5	100% / 28 days	1 g/g	1.69 g/g	1.82 g/g	0.73 log Pow	1.48 log BCF	0.788 log Koc
6	90.4% / 28 days	—	—	—	0.81 log Pow	0.5 log BCF	—

**Other Adverse Effects** No additional information available.

### SECTION 13 - DISPOSAL CONSIDERATIONS

**Waste Disposal** Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

**Waste Disposal of Packaging** An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

**Landfill Precautions** Not available

**Incineration Precautions** \*\* DO NOT INCINERATE \*\* CONTENTS UNDER PRESSURE \*\*

### SECTION 14 - TRANSPORTATION INFORMATION

<u>Transportation Information</u>	<u>Ground Transportation (DOT)</u>	<u>Air Transportation (IATA)</u>	<u>Ocean Transportation (IMDG)</u>
UN Number	UN1950	UN1950	UN1950
Proper Shipping Name	Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity
Hazard Class(es)	2.1	2.1	2.1
Packaging Group	—	—	—
Marine Pollutant	No	No	No
Hazard Label(s)			





# SAFETY DATA SHEET

Part No. N7460CT Aerosol

January 4, 2019

Revision 2

Page 7 of 7

## Prima Marc Blue Marking Dye

### SECTION 15 - REGULATORY INFORMATION

#### Federal Regulations

ID	TSCA LISTED	SARA 302 EHS TPQ	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	SARA 311/312 ACUTE	CHRONIC	PRESSURE	CLEAN AIR ACT HAP	CLEAN AIR ACT SOCMI	CLEAN WATER ACT
1	Yes	-	-	-	-	Yes	-	-	-	-	-	-	-
2	Yes	-	-	-	-	Yes	-	-	-	-	-	-	-
3	Yes	-	U154	5000	3%	Yes	-	Yes	-	-	Yes	Yes	-
4	Yes	-	U002	5000	-	Yes	-	Yes	-	-	-	-	-
5	Yes	-	U112	5000	-	Yes	-	Yes	-	-	-	-	-
6	Yes	-	-	-	-	-	-	Yes	-	-	-	-	-

#### State Regulations

ID	CA P-65	DE RQ	MA RTK CODES	ME TYPE	ME RQ	ME RTK	MN AIR	MN WATER	NJ RTK	NJ AIR	NY LAND	NY ACUTE	PA LISTED	WA PEL TWA	WI TABLE	WV TAP
2	-	-	2,4,5,6 * T1*	-	-	AO	-	-	-	-	-	-	Yes	1000 ppm	-	-
3	D	5000	2,4,5,6 F8 F9	-	2000	ANO	1	-	-	5000	1	-	Yes-E	200 ppm	-	-
4	-	5000	2,4,5,6 F8 F9	-	20000	AON	-	-	-	5000	1	-	Yes-E	750 ppm	-	-
5	-	5000	2,4,5,6 F8	-	20000	AO	-	-	-	5000	1	-	Yes-E	400 ppm	-	-
6	-	-	2,4,6 F8	-	-	AO	-	-	-	-	-	-	Yes	25 ppm	A	-

### SECTION 16 - OTHER INFORMATION

#### SDS Revision History

Revision 1, 07/05/2016, Original in GHS Version 3 Format.

#### SDS Compliance

This SDS complies with the below listed regulations only.

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200  
Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

#### Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.